

Specialty Codes

	ULTRAPURE		P200 OPTIONS		SANIFLO
	CSA		U.L. LISTED		DRUM PUMP
	OBSOLETE		OEM		PCM I
	WIL-GUARD		SINGLE POINT		800 OPTIONS

Specialty Code	Description
2	Unpainted (aluminum & cast iron ONLY)
3	OBSOLETE (was Spark-free)
4	OBSOLETE (was Spark free, unpainted)
6	Diaphragms, dome shaped
9	Exhaust port facing down
10	OBSOLETE (was S.S. outer piston, spark free)
14	BSP
15	OBSOLETE (was Spark free, BSP)
17	BSP, unpainted
18	Wing nuts, BSP, unpainted
19	OBSOLETE (was Spark free, BSP, unpainted)
22	External S.S. fasteners and hardware
23	Wing nuts
24	External S.S. fasteners and hardware, BSP
26	External S.S. fasteners and hardware, unpainted
27	External S.S. fasteners and hardware, BSP, unpainted
28	External S.S. fasteners and hardware, S.S. outer piston, BSP
29	Air valve kit w/ oil bottle
30	Screen based
31	Screen based, S.S. clamp bands and fasteners
32	Screen based, unpainted
33	OBSOLETE (was Screen based, spark free)
34	Screen based w/POLY screen, BSP
35	OBSOLETE (was Screen based, spark free, unpainted)
36	Screen based, BSP
37	OBSOLETE (was Screen based, spark free, BSP)
38	OBSOLETE (was Screen based, spark free, BSP, unpainted)
39	Screen based, w/ Polyurethane screen
40	Bolted, ANSI flange
41	Bolted, DIN flange
42	Bolted, ANSI flange, unpainted
43	Bolted, DIN flange, unpainted
44	Stallion, balls & seats ONLY
45	Stallion, shaft & bumpers ONLY
46	Stallion, internals, BSP

47	Stallion, Externals, Balls & Seats
48	Stallion, internals
49	Stallion, w/ aluminum screen / Atex Available
50	Stallion
51	Stallion, BSP
52	No longer available
53	Stallion, footed, BSP
54	Stallion, footed
55	STALLION, EXTERNALS, BALLS & SEATS, BSP
56	Stallion, w/ vendor #831 (WABCO) diaphragms
57	M20, w/ undrilled drain holes
58	OBSOLETE
59	Stallion, w/ vendor #831 (WABCO) diaphragms, BSP
60	USE - 062 OR 063
61	Stallion, w/ aluminum screen ,BSP/ Atex Available
62	High Pressure, ANSI flange (Parts Only)
63	High Pressure, DIN flange
64	REQUIRES AN RR (Stallion, w/ turbo air valve ONLY)
65	Stallion Shaft (Parts ONLY)
66	High Pressure, ANSI flange, Standard air valve
67	Food Processing, Wil-Gard 220V
68	Food Processing, vertical flange
69	Food Processing, vertical flange, w/ stand
70	Food Processing
71	Food Processing, w/ stand
72	Food Master
73	Sani-Flo USDA 6" Discharge VC only
74	Food Master, w/ stand
75	Food Processing, Stallion Balls and Seats ONLY
76	Food Processing, Stallion internals
77	Tri-Clamp Fittings, Wil-Gard 110V
78	Tri-clamp fittings, PFA Coated
79	Tri-clamp fittings, wing nuts
80	Tri-clamp fittings
81	OBSOLETE - USE 080
82	Food Master, 2-1/2" balls
83	LSH, Sanitary
84	LSH, sanitary, center ported
85	Sanitary (3A) CIP, Wil-Gard 110V
86	Sanitary (3A) CIP, Wil-Gard 220V
87	LSH, sanitary, side ported
88	Air valve kit, threaded connection (Stallion shaft)
89	Air valve kit, threaded connection
90	U.L. Approved

91	U.L. Approved, Wil-Gard 110V
92	U.L. Approved, screen based
93	OBSOLETE - USE 090
94	U.L. Approved, unpainted
95	U.L. Approved, screen based, unpainted
96	U.L. Approved with VRV
97	U.L. Approved with VRV, Screen based
98	U.L. Approved with VRV, unpainted
99	U.L. Approved with VRV, Screen based, unpainted
100	Wil-Gard 110V
101	Wil-Gard 110V, unpainted
102	Wil-Gard sensor wires ONLY
103	Wil-Gard 220V
106	Wil-Gard sensor wires ONLY, DIN Flange
107	BSP, Wil-Gard sensor wires ONLY, unpainted
108	BSP, Wil-Gard 220V
111	Stallion, internals, unpainted
112	OBSOLETE (was Stallion, internals, spark free)
113	OBSOLETE (was Stallion, internals, spark free, BSP)
114	Stallion handles ONLY
115	Same as 113
116	Stallion, BSP, w/o handles
117	Same as 046
118	Stallion, balls & seats ONLY, BSP
119	Food Master, 2-1/2" Balls, w/ stand
120	Food Processing, Wil-Gard 110V
121	Food Processing, Wil-Gard 110V, w/ stand
122	Food Processing, Wil-Gard Wires ONLY
123	Food Processing, Pump Cycle Monitor I (Module, sensor & wires)
124	Food Processing, Accu-Flo, 24V DC, International, PTB approved
125	Food Processing, Accu-Flo, 24V DC coil
126	Food Processing, Accu-Flo, 24V DC x-proof coil
127	Food Processing, Accu-Flo, 110V AC coil
128	Food Processing, Accu-Flo, 24V AC / 12V DC coil
129	Food Processing, Accu-Flo, 24V AC / 12V DC x-proof coil
130	Food Processing, Accu-Flo, 110V AC x-proof coil
138	Accu-Flo 24V DC, Tri-Clamp Fittings & Wingnuts
139	Accu-Flo 110V AC x-proof coil, Tri-Clamp fittings & Wing nuts
140	OBSOLETE - Accu-Flo, 110V AC coil, lube-free center section
141	Accu-Flo, Valve Body Only, no coil
142	Accu-Flo, valve body only, no coil, BSP, discharge manifold facing air inlet
143	Accu-Flo, 110V AC x-proof coil, BSP
144	Accu-Flo, 110V AC coil, BSP
145	Accu-Flo, 110V AC x-proof coil, Wil-Gard 110V

146	REQUIRES AN RR (Accu-Flo, 220V AC x-proof coil)
147	OBSOLETE (was Accu-Flo, 24V DC coil, spark free, BSP)
148	Accu-Flo, valve body only, no coil, BSP
149	Accu-Flo, x-proof valve body only, no coil, BSP
150	Accu-Flo, 24V DC coil
151	Accu-Flo, 24V AC / 12V DC coil
152	OBSOLETE - Accu-Flo, 24V AC / 12V DC coil, lube-free center section
153	Accu-Flo, 24V AC / 12V DC x-proof coil
154	Accu-Flo, 24V DC x-proof coil
155	Accu-Flo, 110V AC coil
156	Accu-Flo, 110V AC x-proof coil
157	Accu-Flo, 24V DC coil, International, PTB approved
158	Accu-Flo, 24V DC coil, International, PTB approved, BSP
159	Accu-Flo, 24V DC coil, International, PTB approved, DIN flange
160	Accu-Flo, 24V DC coil, BSP
161	Accu-Flo, 24V DC x-proof coil, BSP
162	Accu-Flo, 24V AC / 12V DC coil, BSP
163	Intrinsically Safe Coil (Parts ONLY)
164	Accu-Flo, 110V AC coil, Wil-Gard sensor wires ONLY
165	OBSOLETE - Accu-Flo, 24V DC coil, lube-free center section
166	Accu-Flo, 24V DC coil, Wil-Gard 110V
167	Accu-Flo, 24V AC / 12V DC coil, Wil-Gard 110V
168	Accu-Flo, 110V AC coil, Wil-Gard 110V
169	Accu-Flo, 110V AC coil, PFA coated
170	Accu-Flo, 110V AC x-proof coil, PFA coated
171	Accu-Flo, 110V AC, PFA Coated, Wil-Gard Sensor Wires
172	Accu-Flo, 24V AC/12V DC x-proof coil, PFA coated, Wil-Gard 110V
173	Accu-Flo, 110V AC coil, UP male connection
174	Accu-Flo, 110V AC x-proof coil, UP male connection
175	Accu-Flo, 24V DC coil, BSP, discharge & inlet facing exhaust
176	Accu-Flo, 110V AC coil, UP male connection, PFA coated
177	Accu-Flo, 110V AC x-proof coil, UP male connection, PFA coated
178	Accu-Flo, 24V AC / 12V DC coil, Wil-Gard wires ONLY
179	Accu-Flo, 24V AC/12V DC x-proof coil, Wil-Gard Cables ONLY.
180	Accu-Flo, 24V AC / 12V DC coil, PFA coated
181	Accu-Flo, 24V AC / 12V DC x-proof coil, PFA coated
182	Accu-Flo, 24V DC, x-proof coil, Wil-Guard cables installed
183	Accu-Flo, 24V AC / 12 V DC x-proof coil, Wil-Gard 110V
184	Accu-Flo, 24V DC coil, PFA coated
185	Accu-Flo, 24V DC x-proof coil, PFA coated
186	Accu-Flo, 24V AC / 12V DC coil, UP male connection
187	Accu-Flo, 24V AC / 12V DC x-proof coil, UP male connection
188	Accu-Flo, 24V AC / 12V DC coil, UP male connection, PFA coated
189	Accu-Flo, 24V AC / 12V DC x-proof coil, UP male connection, PFA coated

190	Accu-Flo, 24V DC coil, UP male connection
191	Accu-Flo, 24V DC x-proof coil, UP male connection
192	Accu-Flo, 24V DC coil, UP male connection, PFA coated
193	Accu-Flo, 24V DC x-proof coil, UP male connection, PFA coated
194	OBSOLETE (was Accu-Flo, 24V DC coil, spark free)
195	OBSOLETE (was Accu-Flo, 24V DC x-proof coil, spark free)
196	OBSOLETE (was Accu-Flo, 24V AC / 12V DC coil, spark free)
197	OBSOLETE (was Accu-Flo, 24V AC / 12V DC x-proof coil, spark free)
198	OBSOLETE (was Accu-Flo, 110V AC coil, spark free)
199	OBSOLETE (was Accu-Flo, 110V AC x-proof coil, spark free)
200	Lube-free (PARTS ONLY)
206	PFA coated, Wil-Gard sensor wires ONLY
220	Discharge manifold with 1-1/2" NPT and 440 hardened SS seats
221	Exhaust port facing down, inlet facing air valve, (90' elbow)
222	Inlet manifold facing air inlet
225	Turbo (PARTS ONLY)
226	Stallion Balls & Seat & Handles
227	Phenolic air valve piston
228	Phenolic air valve piston, unpainted
229	OBSOLETE (was Phenolic air valve piston, spark free)
230	SS Outer Pistons, BSP
231	Stallion, externals (screen & handles)
232	External S.S. fasteners and hardware, S.S. outer piston
233	Stallion, externals (screen & handles), BSP
234	S.S. inner & outer pistons
235	S.S. inner pistons
236	S.S. inner pistons, PFA coated
237	S.S. Inner Piston, Stallion balls and seats
238	USE 22
239	S.S. inner pistons, BSP
240	Discharge & inlet manifolds facing exhaust, Food Processing
241	Same as 245
242	Reverse manifolds, DIN
243	Center ported, 3/4" Discharge and 1" Inlet facing exhaust, NPT
244	Discharge & inlet manifold facing exhaust, BSP, w/Wil-Gard 110V
245	Reverse manifolds
246	Reverse manifolds, BSP
247	Discharge & inlet manifold facing exhaust
248	Discharge and inlet manifolds facing air inlet
249	OBSOLETE (was Discharge manifold facing air inlet, spark free, BSP)
250	Discharge manifold facing air inlet
251	Discharge manifold facing air inlet, BSP
252	S.S. center block w/ aluminum bushing (EXPERIMENTAL)
253	S.S. center block w/ delrin bushing (EXPERIMENTAL)

254	S.S. center block w/ delrin bushing, unpainted (EXPERIMENTAL)
255	Poly center block, w/ delrin bushing
256	Same as 102
257	Same as 100
258	Inlet manifold facing exhaust, Wil-Gard 110V
259	Same as 250
260	Same as 564
261	M2R Champ, Accu-Flo, 24V AC / 12V DC coil
262	M2R Champ, Accu-Flo, 24V AC / 12V DC x-proof coil
263	M2R Champ, Accu-Flo, 24V DC coil
264	M2R Champ, Accu-Flo, 24V DC x-proof coil
265	M2R Champ, Accu-Flo, 110V AC coil
266	M2R Champ, Accu-Flo, 110V AC x-proof coil
271	M2R Champ, Accu-Flo, 110V AC coil, Wil-Gard 110V
272	M2R Champ, Accu-Flo, 24V AC / 12V DC coil, S.S. outer pistons
273	M2R Champ, Accu-Flo, 24V DC coil, Wil-Gard 110V
274	OBSOLETE - M2R Champ, Accu-Flo, 110V AC coil, lube-free center section
275	M2R Champ, Accu-Flo, 24V AC/24V DC coil, Wil-gard 110V
280	Blacoh, Bolted, NPT
281	Blacoh, Bolted, BSP
282	S.S. BSP inlet manifolds and Stallion internals
285	Externally threaded T-section
286	Externally threaded T-section, PFA coated hardware
290	OBSOLETE - Use Specilty Code 294
291	OBSOLETE - DO NOT USE
292	OBSOLETE - DO NOT USE
293	OBSOLETE - Use Specialty Code 295 or 296
294	Enviroguard manifolds, 1-pc inlet clamp bands, stallion balls & seats, w/ brass drain valve
295	Enviroguard manifolds, 1-pc inlet clamp bands, stallion balls & seats, w 1/2" NPT plug
296	Enviroguard manifolds, 1-pc inlet clamp bands, stallion balls & seats, w/ 1-1/2" NPT plug
297	Enviroguard manif, std. bands, Stallion balls & seats, 1-1/2" plug & brass valve (1 ea), no m
298	Enviroguard manifolds, std. bands, stallion balls & seats, 1-1/2" Plug & brass drain valve (1
300	Without air valve
301	OBSOLETE - Without air valve, lube free
302	OBSOLETE - Without air valve, lube-free, BSP
303	Without air valve, turbo
304	Without air valve, DIN flange
305	Without air valve, split manifold
308	Wil-Flo w/Turbo Air Valve, Unpainted - for ARGO Int. (DO NOT PUBLISH)
310	Leak Lock applied to P.025 retainers
315	PFA coated, BSP
317	Single-point Exhaust, SS Hardware
319	Single-point Exhaust, BSP
320	Single-point Exhaust

321	Same as 320
322	Single-point Exhaust, Stallion footed (Balls and seats), BSP
323	Single-point Exhaust, DIN flange
324	Single-point Exhaust, Screen based
325	Single-point Exhaust, Stallion externals
326	Single-point Exhaust, Stallion balls and seats, Stallion handles
327	Single-point Exhaust, Stallion externals, balls & seats
328	Single-point Exhaust, ANSI flange
329	Same as 323
330	Wing nuts, BSP
331	Single-point Exhaust, Screen Base, BSP
332	Single-point Exhaust, Stallion Balls & Seats, BSP
333	Single-point Exhaust, Screen Base, S.S. Hardware
334	Single-point Exhaust, Polyurethane Screen Base
335	Food Processing w/ threaded Inlet T-section for Drum Pump
336	Single-point Exhaust, Stallion w/o Handles (polyurethane screen and stallion balls & seats)
337	Single-point Exhaust, Screen Based w/ Polyurethane screen, BSP
338	Single-point Exhaust, Stallion externals, balls & seats, check ball assy, BSP
339	Single-point Exhaust, Stallion Balls & Seats
340	Screen based, S.S. clamp bands and fasteners, BSP
341	Single-point Exhaust, Food Processing
342	Single-point Exhaust, LSH Sanitary, Center ported
343	Single-point Exhaust, Screen Based, Stallion balls & seats
344	Single-point Exhaust, Stallion balls, seats and handles, check ball assy, BSP
345	Single-point Exhaust, Stallion externals, balls & seats, check ball assy, BSP, Anodized AV a
346	Single-point Exhaust, Stallion balls, seats & handles, check ball assy, BSP, Anodized AV as
347	Single-point Exhaust, Stallion balls & seats, BSP, Anodized AV assy
348	Single-Point Exhaust, Stallion Externals, Balls & Seats, BSP
349	Single point exhaust, Stallion externals, balls, seats and Alum screen - ATEX version
350	Reserved for ARGO
351	Sani-Flo (3A) style pump w/ Pro-Flo c-sec and no Wil-Gard - REQ. AN RR
354	PV4-PV15 Stainless Steel Air Valve with Anodized Spool
355	Anodized Air Valve
356	Single-Point Exhaust, Anodized Air Valve
360	Accu-Flo, 24V DC coil, DIN flange
361	Same as 150
362	Accu-Flo, 110V AC coil, PFA coated, Wil-Gard 110V
363	Stallion, internals (balls & seats ONLY), Accu-Flo, 110V AC coil
364	Stallion, internals (balls & seats ONLY), Accu-Flo, 24V AC / 12V DC coil
365	Stallion Internals (balls & seats ONLY), Accu-Flo, 24V DC coil
366	Stallion Footed w/ Handles & Stallion shaft & bumper only (standard balls & seats)
367	Stallion, balls & seats ONLY, Tri-clamp fittings, wing nuts
368	STALLION, (BALLS & SEATS ONLY) ACCU-FLO, 24V AC / 12V DC COIL
371	Same as 151

372	Same as 153
373	Same as 154
374	Same as 155
375	Same as 156
376	Bottled, Accu-Flo, 24V DC, International, PTB approved
377	Same as 360
378	Accu-Flo, 24V AC / 12V DC coil, DIN
379	Accu-Flo, 24V AC / 12V DC x-proof coil, DIN
380	Accu-Flo, 24V DC x-proof coil, DIN
381	Accu-Flo, 110V AC coil, DIN
382	Accu-Flo, 110V AC x-proof coil, DIN
383	Same as 159
385	P2 EHEDG (3A Design, with Pro-Flo ADS and no Wil-Gard)
386	EHEDG DN Connection
387	EHEDG SMS Connection
390	Built to CSA Specifications
391	Built to CSA Specifications, 1" NPT center ported inlet and discharge manifolds
392	Built to CSA Specifications
393	Built to CSA Specs, Center Ported NPT (1" Inlet facing air inlet, 3/4" discharge facing exhaust)
394	Built to CSA Specs, Center Ported NPT (1" inlet facing exhaust, 3/4" discharge facing air inlet)
395	Groundable Liquid Chamber and Center Section assy.
400	M2R Champ
402	M2R Champ, PFA coated
404	M2R Champ, DIN flange
406	M2R Champ, DIN flange, PFA coated
407	OBSOLETE - M2R Champ, without air valve, lube-free
415	M2R Champ, Wil-Gard sensor wires ONLY
416	M2R Champ, PFA coated, Wil-Gard sensor wires ONLY
417	OBSOLETE - M2R ANSI ONLY (lube-free center section w/turbo air valve)
420	M2R Champ, Wil-Gard 110V
422	use 423
423	M2R Champ, PFA Coated, Wil-Gard 110V
424	M2R Champ, DIN flange, Wil-Gard 220V
426	M2R Champ, DIN flange, PFA coated, Wil-Gard 220V
428	M2R Champ, Wil-Gard 220V
430	M2R Champ, S.S. outer pistons
435	P2R w/Threaded T-section and Flaretek Fittings, Pump to be Built in Clean Room
451	M2R Champ, Accu-Flo, no coil, DIN flange
454	M2R Champ, Accu-Flo, 24V DC coil, DIN flange
455	M2R Champ, Accu-Flo, 24V AC / 12V DC coil, DIN flange
456	M2R Champ, Accu-Flo, 24V DC coil, International, PTB approved, DIN flange
457	M2R Champ, Accu-Flo, 24V DC coil, DIN flange, S.S. outer piston
458	M2R Champ, Accu-Flo, 24V DC coil, DIN flange, Wil-Gard 220V
460	Same as 502

461	Same as 506
465	Versa Retrofit Kit
480	Pump Cycle Monitor I (Sensor & wires only)
481	NPT Threaded Pro-Flo Endcap (Pilot Plug Required)
482	Pump Cycle Monitor I (Sensor & wires only), BSP
483	Pump Cycle Monitor I (Module, sensor & wires)
484	Pump Cycle Monitor I (Module, sensor & wires), BSP
485	Pump Cycle Monitor I (Module, sensor & wires), DIN Flange
486	Pump Cycle Monitor I (Module, sensor & wires), w/Stallion balls & seats
487	Pump Cycle Monitor I, (Sensor & wires only), DIN Flange
488	Pump Cycle Monitor (sensor & wires only), M2R Champ
490	Pro-Flo with 1/8" NPT Exhaust hole
492	U.L. Listed, Side Ported, Single-point Exhaust
493	UL Listed, Center ported NPT (1" inlet facing air, 3/4" disch facing exhaust), Single-point Ex
494	UL Listed, Center ported NPT (1" inlet facing exhaust, 3/4" disch facing air), Single-point Ex
495	UL Listed, Single-point exhaust center section
500	Champ (PARTS ONLY)
501	Adapter block, no muffler, Pro-Flo center section, PFA coated hardware
502	PFA coated
503	ANSI flange (P200 metal only)
504	DIN flange
506	DIN flange, PFA coated
507	OBSOLETE - Vertically ported auto block, no muffler, lube free center section, manifolds fa
508	Vertically ported auto block, Accu-flo inner pistons, manifolds facing exhaust & bands at 2 d
509	Adapter block, no muffler, P2R, center section
510	PVDF end caps, PFA coated
511	Acetal end caps, PFA coated
512	Adapter block, no muffler, Pro-Flo, center section
513	S.S. outer pistons
514	Adapter block, no muffler, standard center section
515	REQUIRES AN RR (PVDF discharge elbows & tee sections)
516	Adapter block, no muffler, turbo center section
517	OBSOLETE - Adapter block, no muffler, lube-free center section
518	Adapter block, no muffler, M2R, turbo center section
519	OBSOLETE - Adapter block, no muffler, M2R, lube-free center section
520	Ultrapure II, female connections
521	Ultrapure II, female connections, PFA coated
522	Ultrapure II, male bondable connections
523	Ultrapure II, male bondable connections, PFA coated
524	Ultrapure II, male bondable connections, Wil-Gard 110V
525	Ultrapure II, female connections, PFA coated, Wil-Gard sensor wires ONLY
526	Ultrapure II, female connections, PFA coated, Discharge & inlet manifold facing exhaust
527	Ultrapure II, female connections, PFA coated, Wil-Gard 110V
530	Ultrapure II, female connections, Wil-Gard 110V

531	Ultrapure II, female connections, Wil-Gard sensor wires ONLY
532	Ultrapure II, male bondable connections, PFA coated, Wil-Gard 110V
533	Ultrapure II, male bondable connections, PFA coated, Wil-Gard 220V
534	Ultrapure II, female connections, Accu-Flo 110V, PFA coated
535	Ultrapure II, female connections, Accu-Flo 24V AC/12V DC, PFA coated
536	Ultrapure II, female connections, Accu-Flo 24V AC/12V DC
538	Adapter Block, No Muffler, Turbo Center Section, Dish Manifolds Facing Air Inlet
552	Center Ported, BSPT (1" Inlet facing exhaust & 3/4" disch facing air inlet), adapter blk, no m
553	Center & Vertically ported NPT manifolds, Adapter block, no muffler, standard center sectio
554	Adapter block, no muffler, Pro-Flo center section, BSP
555	Adapter block, no muffler, Pro-Flo center section, Tri-Clamp flanges & Wingnuts
556	Adapter block, no muffler, turbo center section, BSP
557	Adapter block, no muffler, standard center section, BSP
558	Adapter block, no muffler, T2R, Turbo center section, DIN flange
559	Adapter block, no muffler, P2R center section, DIN flange
560	Split manifold
561	Split manifold, PFA coated
562	Split Manifold, BSP
563	Split manifold, discharge only
564	Split manifold, inlet only
565	Split manifold, food grade bands
567	Split manifold, Accu-Flo, 24V DC coil
568	Split manifold, wing nuts
569	Split manifold, inlet only, BSP
570	Split manifold, Accu-Flo, 24V AC / 12V DC coil
580	Same as 560
590	P2R Poly/TNU or Poly/WFS - Refer to Assembly Work Instruction ASM 14-INTEL
591	P.025 Poly/TX & Kynar/TX - Refer to Assembly Work Instruction ASM 14-INTEL-00
603	PFA coated, Wil-Gard 110V
604	DIN flange, Wil-Gard 220V
606	DIN flange, PFA coated, Wil-Gard 220V
608	PFA coated, Wil-Gard 220V
612	Ultrapure (T1 & T4 champ), male bondable connections, PFA coated
618	Ultrapure (T1 & T4 Champ), male bondable connections, PFA coated, Wil-Gard 110V
622	Ultrapure (T1 & T4 Champ), male bondable connections
623	Ultrapure (T1 & T4 Champ), male bondable connections, adapter block, no muffler
624	Ultrapure (T1 & T4 Champ), male bondable connections, Wil-Gard 110V
630	With Krytox Oil (Parts ONLY)
640	Flaretek Fittings
641	Flaretek Fittings, PFA coated
645	Fittings, Hose Barb Connection
650	Show / Photo Shoot - NOT FOR SALE
651	Vertically Ported Discharge, NPT
652	Vertically Ported Discharge, BSPT

660	Split manifold, Wil-Gard 110V
661	Split manifold, PFA coated, Wil-Gard 110V
662	Split manifold, Accu-flo, 110V AC coil
663	Split manifold, adapter block, no muffler, Pro-Flo , center section
664	Center and Vertical ported manifolds, NPT - NO PLUGS
665	Center and Vertically ported manifolds, BSPT - NO PLUGS
667	Center and Vertically ported manifolds, NPT
668	Center and Vertically ported manifolds, BSPT
669	Center-ported inlet & vertical-ported discharge, NPT
670	Vertically ported, inlet manifold only, NPT
671	Vertically ported, inlet manifold only, BSP
672	Vertically ported, inlet and discharge manifolds, NPT
673	Vertically ported, inlet and discharge manifolds, BSP
674	Accu-Flo 110V AC, vertically ported inlet manifold only, NPT
675	Accu-Flo, 24V DC, vertically ported, inlet manifold only, NPT
676	Accu-Flo, 24V DC, vertically ported, inlet manifold only, BSP
677	Center Ported, NPT Inlet & Discharge
678	Center Ported, BSPT Inlet & Discharge
679	Accu-Flo 24V AC/12V DC, Vertically ported inlet and discharge, NPT
680	P100 with OEM Specific Inlet Manifold
682	P100 with OEM manifold, Accu-Flo 24V DC Coil
683	P100 with OEM Specific Inlet Manifold, center ported inlet and discharge manifolds, NPT
684	P100 with OEM Inlet Manifold reversed, Accu-Flo 24V DC Coil & bronze muffler
685	Center Ported, NPT Inlet & Discharge, PCM Sensor & Wires
686	Accu-Flo 24V AC/12V DC, Center Ported NPT Inlet & Discharge, Wil-Gard wires only
687	Center Ported, NPT Inlet & Discharge, Single-point Exhaust
688	Center Ported, BSPT Inlet and Discharge manifolds, Single-point Exhaust
689	Center Ported, NPT inlet and discharge with external SS fasteners
690	Center Ported ANSI/DIN Combo
691	Center ported, ANSI/DIN combo flange, PFA Coated fasteners
692	Accu-flo 24V AC/12V DC, Center Ported (1" inlet facing exhaust, 3/4" disch. facing air inlet)
693	CENTER PORTED NPT, PFA COATED
694	Accu-Flo 24V AC/12V DC, Ctr Ported (1" inlet facing air, 3/4" disch. facing exhaust), coil ups
695	Center Ported Drop-in (1" inlet facing air inlet & 3/4" discharge facing exhaust)
696	Center Ported Drop-in, BSPT (1" inlet facing air inlet & 3/4" discharge facing exhaust)
697	Center Ported Pro-Flo Drop-in (1" Inlet facing exhaust & 3/4" discharge facing air inlet)
698	Center Ported Pro-Flo Drop-in, BSPT (1" inlet facing exhaust & 3/4" discharge facing air inlet)
699	Center Ported, BSPT (1" inlet facing exhaust & 3/4" disch facing air inlet), Wil-Gard sensor
700	Pro-Flo (PARTS ONLY)
702	Pro-Flo®, BSP (PARTS ONLY)
703	C-Section with SS Hardware
705	P4/P400 with Closed Spool A.V. - RR only
720	P2 Hybrid Bolted, NPT
721	P2 Hybrid Bolted, BSP

722	P2 Hybrid Bolted, Food Processing
723	P2 Hybrid Bolted, BSP, 24V DC coil
724	A2P Hybrid Bolted, 24V AC/12V DC coil
725	A2P Hybrid Bolted, BSP, 24V AC/12V DC coil, Wil-Gard 220V
726	P2 Hybrid Bolted, Tri-clamp fittings
727	P2 Hybrid Bolted, NPT, Wil-Gard sensor wires ONLY
728	A2P Hybrid Bolted, 24V DC x-proof coil
730	Side Ported, NPT inlet & discharge
731	Center Ported, ANSI/DIN Combo, w/PCM (sensor & wires only)
732	SIDE PORTED, NPT INLET & DISCHARGE, SINGLE-POINT EXHAUST
733	Center Ported, Reversed ANSI/DIN combo (inlet facing air inlet/discharge facing exhaust)
734	Center Ported, Reversed ANSI/DIN combo (inlet facing air inlet/disch facing exhaust), PFA
735	Center Ported, NPT (1" inlet facing air inlet, 3/4" disch. facing exhaust), Single-point Exhaust
736	Center Ported BSPT (1" inlet facing air inlet, 3/4" disch. facing exhaust), Single-point Exhaust
737	Center Ported, NPT (1" inlet facing exhaust, 3/4" disch. facing air inlet), Single-point Exhaust
738	Center Ported, BSPT (1" inlet facing exhaust, 3/4" disch. facing air inlet), Single-point Exhaust
739	CENTER PORTED ANSI/DIN COMBO WITH WIL-GARD 110V
740	Obsolete - Use specialty code 0741
741	Accu-Flo 24V DC, Center ported (1" inlet facing exhaust, 3/4" discharge facing air inlet)
742	Accu-Flo 110V AC, Center Ported (1" inlet facing exhaust, 3/4" discharge facing air inlet)
743	Obsolete - Use specialty code 0746
744	Accu-Flo 24V AC/12V DC, Center Ported, 1" NPT inlet and discharge
745	Accu-Flo 24V DC, Ctr ported (1" inlet facing exhaust, 3/4" disch facing air inlet), Wil-Gard W
746	Accu-Flo, 24V DC, Center Ported BSPT (1" inlet facing exhaust, 3/4" disch facing air inlet)
747	Accu-Flo 24VDC X-Proof, Cntr port ProFlo drop in 1" inlet facing exh & 3/4" dischrng facing a
748	Accu-Flo, 24V DC X-Proof Coil, Center Ported 1" NPT Inlet and Discharge
749	Accu-Flo, 24V DC X-Proof Coil, Center Ported 1" BSPT Inlet and Discharge
750	Cast iron INLET manifold
760	ATEX Approved
761	Accu-Flo, ATEX Approved, 24V DC
762	Accu-Flo, ATEX Approved, 24V DC, BSP
763	Accu-Flo, ATEX Approved, 24V DC, DIN Flange
764	ATEX Approved, Tri-clamp fittings & wing nuts
765	ATEX Elastomer Kits
766	Accu-Flo, ATEX 24V DC, Center ported Pro-Flo drop-in(1" Inlet facing exhaust, 3/4" disch fa
767	Accu-Flo, ATEX 24V DC, Center Ported, BSPT (1" Inlet facing exhaust, 3/4" disch facing air-
768	Adapter Block, No Muffler, PX Center Section, BSPT
770	SaniFlo HS
771	SaniFlo HS, w/Swivel Stand
772	SaniFlo HS, Wil-Gard 110V
773	SaniFlo HS, Wil-Gard 220V
774	SaniFlo HS, Wil-Gard 110V, w/Swivel Stand
775	SaniFlo HS, Wil-Gard 220V, w/Swivel Stand
776	SaniFlo HS, Horizontally Mounted

777	SaniFlo HS for DUS (same as 0770 without inlet connections)
778	Saniflo HS, DIN25 Connection
779	Saniflo HS, w/swivel stand, DIN25 connection
780	Saniflo HS, Wil-Gard 110V, DIN25 connection
781	Saniflo HS, Wil-Gard 220V, Din25 connection
782	Saniflo HS, Wil-Gard 110V, w/swivel Stand DIN25 connection
783	Saniflo HS, Wil-Gard 220V, w/swivel stand, DIN25 connection
784	Saniflo HS, SMS connection
785	Saniflo HS, w/swivel stand, SMS connection
786	Saniflo HS, Wil-Gard 110V, SMS connection
787	Saniflo HS, Wil-Gard 220V, SMS connection
788	Saniflo HS, Wil-Gard 110V, w/swivel stand, SMS connection
789	Saniflo HS, Wil-Gard 220V, w/swivel stand, SMS connection
790	P100 Advanced, drum pump inlet manifold
800	Barb Hose Connection
900	BioPharm
901	BioPharm, BSP
902	BioPharm, DIN
903	BioPharm, FDA (tri-clamp flanges & wingnuts)
904	BioPharm, USDA (Food Master)
905	BioPharm, CIP (3A "Style" with out Wil-Gard)
907	BioPharm, LSH, Side Ported
908	BioPharm, FDA, Accu-Flo, 24V DC
909	BioPharm, FDA, Accu-Flo, 24V DC, X-proof
910	BioPharm, FDA, Accu-Flo, 24V AC/12V DC
911	BioPharm, FDA, Accu-Flo, 24V AC/12V DC, X-proof
912	BioPharm, FDA, Accu-Flo, 110V AC
913	BioPharm, FDA, Accu-Flo, 110V AC, X-proof
914	BioPharm, Accu-Flo, 24V DC
915	BioPharm, Accu-Flo, 24V AC/12V DC
916	BioPharm, Accu-Flo, 24V AC/12V DC, X-proof
917	BioPharm, Accu-Flo, 24V DC, X-proof
918	BioPharm, Accu-Flo, 110V AC
919	BioPharm, Accu-Flo, 110V AC, X-proof